



SAQ
S.I.A.T.
sec. Pittarc

TECHNICAL SPECIFICATIONS
GMAW WELDING WIRE
TRADE NAME : PITTARC GS2

Document SPPXXX
Revision 0 i
Data 28.03.10
Page 1 / 1

1. DESCRIPTION

Gas shielded welding wire in according to standard UNI EN ISO 14341-A-G2Ti and AWS A5.18 ER70S-2 suitable to join on all grades of mild and carbon steels, producing quality welds with minimal porosity. It is a triple deoxidized wire (Zirconium, Titanium, and Aluminum) making it an excellent choice for welding over rust or dirty surface, mill scale and galvanized plates.

2. PRODUCT CHEMICAL COMPOSITION (%)

		C	Mn	Si	P	S	Cr	Ni	Mo	Zr	Ti	Al
PITTARC GS2	min	0.04	0.90	0.40	-	-	-	-	-	0.02	0.05	0.05
	max	0.07	1.70	0.70	0.025	0.025	0.15	0.15	0.15	0.12	0.12	0.15
EN ISO 14341-A- G2Ti	min	0.04	0.90	0.40	-	-	-	-	-	0.05		0.05
	max	0.14	1.20	0.80	0.025	0.025	0.15	0.15	0.15	0.25		0.20
AWS A5.18 ER70S-6	min	-	0.90	0.40	-	-	-	-	-	0.05	0.02	0.05
	max	0.07	1.40	0.70	0.025	0.035	0.15	0.15	0.15	0.15	0.12	0.15

3. WIRE DIMENSIONS

Standard diameter (mm) : 0.8 ; 1.0 ; 1.2 ; 1.4 ; 1.6
Permissible deviations : ISO 544

4. CAST AND HELIX (STANDARD PACKAGING)

Cast (mm) : 800 ÷ 1000
Helix (mm) : maximum 10

5. ALL-WELD-METAL MECHANICAL PROPERTIES

	Re MPa	Rm MPa	A5 %	KV (-20°C) J
AWS A5.18 ER70S-2	≥ 400	≥ 480	≥ 22	-
PITTARC GS2	≥ 440	≥ 520	≥ 26	≥ 47

Gas protection : ISO 14175 C1 (CO₂) / ISO 14175 M21 (80% Ar + 20% CO₂).

Classification : EN ISO 14341-A- G 42 2C GS2 / EN ISO 14341-A- G 42 4M GS2

6. STANDARD PACKAGING.

Wire basket rim RG (ISO 544 B300) of 18 kg net weight. Each spool sealed in a polyethylene airtight bag and packed into a cardboard box. 72 spools stacked onto a pallet secured by thermoplastic shrink-wrapping (94x125x80 cm, 1296kg net weight). Available cardboard drums of about 250kg net weight, each one stacked onto a pallet 105x105x90 cm of about 1000kg total weight, secured by thermoplastic shrink-wrapping. On request packaging available from 15 kg up to 700 kg.

7. STANDARD IDENTIFICATION.

A label is attached to the inside of each spool containing nominal diameter, trade name, classification, heat number, operator code. A label is attached to every box containing manufacturer, trade name, nominal diameter, heat number, spool type, references to the standards, CE mark and approvals.

SIAT S.p.A. 33013 Gemona del Friuli (UD) ITALY			
PITTARC GS2			
Welding wire for carbon steels and fine-grained steels EN ISO 14341-A – G42 4M GS2 and AWS A5.18 ER70S-2 Shielding gas according to ISO 14175 M21 Current/Polarity G+, Welding positions: PA-PB-PC-PD-PE-PF-PG			
Weight kg XX	Heat N° XXXXXX/XX	Diameter X,X mm	Spool type X XXX

8. STANDARD CERTIFICATION. Documents according to EN 10204